
DATASHEET - DILM250/22(RA250)



Contactor, 380 V 400 V 132 kW, 2 N/O, 2 NC, RA 250: 110 - 250 V 40 - 60 Hz/110 - 350 V DC, AC and DC operation, Screw connection

Part no.	**DILM250/22(RA250)**
	208201
EL Number (Norway)	**4134083**

General specifications

Product name	Eaton Moeller® series DILM Contactor
Part no.	DILM250/22(RA250)
EAN	4015082082017
Product Length/Depth	208 millimetre
Product height	189 millimetre
Product width	140 millimetre
Product weight	7.065 kilogram
Certifications	CSA Class No.: 3211-04 UL Category Control No.: NLDX IEC/EN 60947-4-1 CSA File No. 1017510 EN 45545: Fire protection on railway vehicles VDE 0660 UL/CSA IEC 61373: Vibration and shock, tested for category 1 class B UL File No.: E29096 UL 60947-4-1 CE marking North America (UL listed, CSA certified)
Product Tradename	DILM
Product Type	Contactor
Product Sub Type	None
Catalog Notes	Conventional thermal current Ith of main contacts (1-pole, open) at 60° EN 45545 - Fire protection on railway vehicles: Fire protection class of all plastics according to UL94: V-0 / plastic weight in total: 1.872 kg Also suitable for motors with efficiency class IE3. Also tested according to AC-3e up to 500 V. Contacts according to EN 50012

General information

Accessories	Fitting options auxiliary contacts: on the side: 2 x DILM820-XHI11(V)-SI; 2 x DILM820-XHI11-SA
Application	Contactors for Motors
Connection	Screw terminals
Degree of protection	IP00
Electromagnetic compatibility	Designed for operation in industrial environments. Its use in residential environments may cause radio-frequency interference, requiring additional noise suppression.
Fitted with:	Suppressor circuit in actuating electronics
Lifespan, electrical	100,000 Operations (at Condensor operation)
Lifespan, mechanical	10,000,000 Operations (DC operated) 10,000,000 Operations (AC operated)
Operating frequency	3000 mechanical Operations/h (DC operated) 3000 mechanical Operations/h (AC operated) 200 Operations/h
Overvoltage category	III
Pollution degree	3
Product category	Contactors
Protection	Finger and back-of-hand proof with terminal shroud or terminal block, Protection against direct contact when actuated from front (EN 50274)
Rated impulse withstand voltage (Uimp)	8000 V AC
Resistance	500 mΩ (Admissible transitional contact resistance - of the external control circuit device when actuating A11)
Shock resistance	10 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms 10 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms 8 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms

Signal level	5 V - 15 V, PLC signal level (A3 - A4) to IEC/EN 61131-2 (type 2), Magnet systems
Utilization category	AC-1: Non-inductive or slightly inductive loads, resistance furnaces AC-3: Normal AC induction motors: starting, switch off during running AC-4: Normal AC induction motors: starting, plugging, reversing, inching
Voltage type	AC/DC

Climatic environmental conditions

Altitude	Max. 2000 m
Ambient operating temperature - min	-40 °C
Ambient operating temperature - max	60 °C
Ambient operating temperature (enclosed) - min	-40 °C
Ambient operating temperature (enclosed) - max	40 °C
Ambient storage temperature - min	-40 °C
Ambient storage temperature - max	80 °C
Climatic proofing	Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78

Terminal capacities

Terminal capacity (busbar)	25 mm width, Main connection
Terminal capacity (copper band)	Fixing with flat cable terminal or cable terminal blocks; See terminal capacity for cable terminal blocks
Terminal capacity (flexible with cable lug)	50 - 240 mm^2
Terminal capacity (flexible with ferrule)	2 x (0.75 - 2.5) mm^2, Control circuit cables 1 x (0.75 - 2.5) mm^2, Control circuit cables
Terminal capacity (solid)	1 x (0.75 - 2.5) mm^2, Control circuit cables 2 x (0.75 - 2.5) mm^2, Control circuit cables
Terminal capacity (solid/stranded AWG)	18 - 14, Control circuit cables 2/0 - 500 MCM, Main cables
Terminal capacity (stranded with cable lug)	70 - 240 mm^2
Width across flats	16 mm
Screw size	M10, Terminal screw, Main connections M3.5, Terminal screw, Control circuit cables
Screwdriver size	2, Terminal screw, Control circuit cables, Pozidriv screwdriver
Tightening torque	24 Nm, Main cable connection screw/bolt 1.2 Nm, Screw terminals, Control circuit cables

Electrical rating

Inrush current	Max. 30 x Ie (peak)
Rated breaking capacity at 220/230 V	2500 A
Rated breaking capacity at 380/400 V	2500 A
Rated breaking capacity at 500 V	2500 A
Rated breaking capacity at 660/690 V	2500 A
Rated breaking capacity at 1000 V	760 A
Rated insulation voltage (Ui)	1000 V
Rated making capacity (cos phi to IEC/EN 60947)	3000 A
Rated operational current (Ie)	220 A at up to 525 V (Individual compensation, three-phase capacitors, open) 133 A at 690 V (Individual compensation, three-phase capacitors, open)
Rated operational current (Ie) at AC-3, 220 V, 230 V, 240 V	250 A
Rated operational current (Ie) at AC-3, 380 V, 400 V, 415 V	250 A
Rated operational current (Ie) at AC-3, 440 V	250 A
Rated operational current (Ie) at AC-3, 500 V	250 A
Rated operational current (Ie) at AC-3, 660 V, 690 V	185 A
Rated operational current (Ie) at AC-3, 1000 V	76 A
Rated operational current (Ie) at AC-4, 220 V, 230 V, 240 V	200 A
Rated operational current (Ie) at AC-4, 440 V	200 A
Rated operational current (Ie) at AC-4, 500 V	200 A
Rated operational current (Ie) at AC-4, 660 V, 690 V	150 A
Rated operational current (Ie) at AC-4, 1000 V	76 A
Rated operational power at AC-3, 240 V, 50 Hz	85 kW
Rated operational power at AC-3, 380/400 V, 50 Hz	132 kW
Rated operational power at AC-3, 415 V, 50 Hz	143 kW
Rated operational power at AC-3, 440 V, 50 Hz	152 kW

Rated operational power at AC-3, 500 V, 50 Hz	173 kW
Rated operational power at AC-3, 690 V, 50 Hz	170 kW
Rated operational power at AC-3, 1000 V, 50 Hz	108 kW
Rated operational power at AC-4, 220/230 V, 50 Hz	62 kW
Rated operational power at AC-4, 240 V, 50 Hz	68 kW
Rated operational power at AC-4, 415 V, 50 Hz	117 kW
Rated operational power at AC-4, 440 V, 50 Hz	125 kW
Rated operational power at AC-4, 500 V, 50 Hz	138 kW
Rated operational power at AC-4, 660/690 V, 50 Hz	137 kW
Rated operational voltage (Ue) at AC - max	1000 V
Rated operational power at AC-4, 1000 V, 50 Hz	108 kW
Safe isolation	500 V AC, Between coil and contacts, According to EN 61140 500 V AC, Between the contacts, According to EN 61140
Special purpose rating of definite purpose rating	2050 A, LRA 480 V 60 Hz 3-ph, 100,000 cycles acc. to UL 1995, (UL/CSA) 300 A, FLA 480 V 60 Hz 3-ph, 100,000 cycles acc. to UL 1995, (UL/CSA) 250 A, FLA 600 V 60 Hz 3-ph, 100,000 cycles acc. to UL 1995, (UL/CSA) 1800 A, LRA 600 V 60 Hz 3-ph, 100,000 cycles acc. to UL 1995, (UL/CSA)

Short-circuit rating

Short-circuit current rating (basic rating)	18 kA, SCCR (UL/CSA) 600 A, max. CB, SCCR (UL/CSA) 700 A, max. Fuse, SCCR (UL/CSA)
Short-circuit current rating (high fault at 480 V)	18/100 kA, Fuse, SCCR (UL/CSA) 700 A, Class L/450 A, Class J, max. Fuse, SCCR (UL/CSA) 700 A, Class L, max. Fuse, SCCR (UL/CSA) 65 kA, CB, SCCR (UL/CSA) 18 kA, Fuse, SCCR (UL/CSA) 250 A, max. CB, SCCR (UL/CSA)
Short-circuit current rating (high fault at 600 V)	18/100 kA, Fuse, SCCR (UL/CSA) 700 A, Class L/450 A, Class J, max. Fuse, SCCR (UL/CSA) 18 kA, CB, SCCR (UL/CSA) 600 A, max. CB, SCCR (UL/CSA) 700 A, Class J, max. Fuse, SCCR (UL/CSA) 18 kA, Fuse, SCCR (UL/CSA)
Short-circuit protection rating (type 1 coordination) at 1000 V	200 A gG/gL
Short-circuit protection rating (type 1 coordination) at 400 V	400 A gG/gL
Short-circuit protection rating (type 1 coordination) at 690 V	400 A gG/gL
Short-circuit protection rating (type 2 coordination) at 1000 V	160 A gG/gL
Short-circuit protection rating (type 2 coordination) at 400 V	315 A gG/gL
Short-circuit protection rating (type 2 coordination) at 690 V	315 A gG/gL

AC-1/Conventional thermal current Ith

Conventional thermal current ith at 40°C (3-pole, open)	430 A
Conventional thermal current ith at 50°C (3-pole, open)	380 A
Conventional thermal current ith at 55°C (3-pole, open)	365 A
Conventional thermal current ith at 60°C (3-pole, open)	350 A
Conventional thermal current ith (3-pole, enclosed)	300 A
Conventional thermal current ith of main contacts (1-pole, open)	875 A
Conventional thermal current ith (1-pole, enclosed)	750 A

Switching capacity

Switching capacity (main contacts, general use)	350 A, Maximum motor rating (UL/CSA)
Switching capacity (auxiliary contacts, general use)	1 A, 250 V DC, (UL/CSA) 15 A, 600 V AC, (UL/CSA)
Switching capacity (auxiliary contacts, pilot duty)	P300, DC operated (UL/CSA) A600, AC operated (UL/CSA)

Magnet system

Behavior in marginal and transitional conditions	Sealing - Voltage drops (0.6 - 0.7 x Uc min: Contactor remains switched on Sealing - Excess voltage (1.15 - 1.3 x Uc max): Contactor remains switched on Sealing - Voltage interruptions 0 - 0.2 x Uc min) > 10 ms: Drop-out of the contactor Sealing - Voltage drops (0.2 - 0.6 x Uc min ≤12 ms: Time is bridged successfully Sealing - Pick-up phase (0.7 x Uc min - 1.15 x Uc max): Contactor switches on with certainty Sealing - Voltage drops (0.2 - 0.6 x Uc min) > 12 ms: Drop-out of the contactor Sealing - Pick-up phase (0 - 0.7 x Uc min: Contactor does not switch on Sealing - Voltage interruptions (0 - 0.2 x Uc min ≤ 10 ms: Time is bridged successfully
Drop-out voltage	0.2 x US max - 0.6 x US min, DC operated AC operated: 0.2 x US max - 0.6 x US min, AC operated

Duty factor	100 %
Pick-up voltage	0.7 - 1.15 V DC x Us 0.7 - 1.15 V AC x Us
Power consumption	Control transformer with uk ≤ 6%
Power consumption, pick-up, 50 Hz	380 VA, Pull-in power, Coil in a cold state and 1.0 x Us 250 W, Pull-in power, Coil in a cold state and 1.0 x Us
Power consumption, pick-up, 60 Hz	250 W, Pull-in power, Coil in a cold state and 1.0 x Us 380 VA, Pull-in power, Coil in a cold state and 1.0 x Us
Power consumption, sealing, 50 Hz	5.5 W, Coil in a cold state and 1.0 x Us 0 CO, Coil in a cold state and 1.0 x Us 10.5 VA, Coil in a cold state and 1.0 x Us
Power consumption, sealing, 60 Hz	10.5 VA, Coil in a cold state and 1.0 x Us 5.5 W, Coil in a cold state and 1.0 x Us
Rated control supply voltage (Us) at AC, 50 Hz - min	110 V
Rated control supply voltage (Us) at AC, 50 Hz - max	250 V
Rated control supply voltage (Us) at AC, 60 Hz - min	110 V
Rated control supply voltage (Us) at AC, 60 Hz - max	250 V
Rated control supply voltage (Us) at DC - min	110 V
Rated control supply voltage (Us) at DC - max	250 V
Switching time (AC operated, make contacts, closing delay) - max	100 ms
Switching time (AC operated, make contacts, opening delay) - max	110 ms

Motor rating

Assigned motor power at 200/208 V, 60 Hz, 3-phase	75 HP
Assigned motor power at 230/240 V, 60 Hz, 3-phase	100 HP
Assigned motor power at 460/480 V, 60 Hz, 3-phase	200 HP
Assigned motor power at 575/600 V, 60 Hz, 3-phase	250 HP

Contacts

Number of auxiliary contacts (normally closed contacts)	2
Number of auxiliary contacts (normally open contacts)	2
Number of contacts (normally closed contacts)	2
Number of contacts (normally open contacts)	2

Design verification

Equipment heat dissipation, current-dependent Pvid	28 W
Heat dissipation capacity Pdiss	0 W
Heat dissipation per pole, current-dependent Pvid	9.33 W
Rated operational current for specified heat dissipation (In)	250 A
Static heat dissipation, non-current-dependent Pvs	5.5 W
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Meets the product standard's requirements.
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of assemblies	Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances	Meets the product standard's requirements.
10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
10.8 Connections for external conductors	Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength	Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage	Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material	Is the panel builder's responsibility.
10.10 Temperature rise	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating	Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Power contactor, AC switching (EC000066)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Power contactor, AC switching (ecl@ss13-27-37-10-03 [AAB718020])			
Rated control supply voltage AC 50 Hz		V	110 - 250
Rated control supply voltage AC 60 Hz		V	110 - 250
Rated control supply voltage DC		V	110 - 250
Voltage type for actuating			AC/DC
Number of normally closed contacts as main contact			0
Number of normally open contacts as main contact			3
Type of electrical connection of main circuit			Rail connection
Operating voltage AC 50 Hz		V	110 - 250
Operating voltage AC 60 Hz		V	110 - 250
Rated operation current Ie at AC-1, 400 V		A	
Rated operation current Ie at AC-3, 400 V		A	250
Rated operation power at AC-3, 400 V		kW	132
Rated operation current Ie at AC-4, 400 V		A	200
Rated operation power at AC-4, 400 V		kW	110
Rated operation power NEMA		kW	149
Number of auxiliary contacts as normally open contact			2
Number of auxiliary contacts as normally closed contact			2
Modular version			No
Width		mm	140
Height		mm	189
Depth		mm	208

© 04/2023 by Eaton Industries GmbH

DATASHEET - DILM300A/22(RA250)



Contactor, 380 V 400 V 160 kW, 2 N/O, 2 NC, RA 250: 110 - 250 V 40 - 60 Hz/110 - 350 V DC, AC and DC operation, Screw connection

Part no.	**DILM300A/22(RA250)**
	139556
EL Number (Norway)	**4134296**

General specifications

Product name	Eaton Moeller® series DILM Contactor
Part no.	DILM300A/22(RA250)
EAN	4015081363346
Product Length/Depth	208 millimetre
Product height	189 millimetre
Product width	140 millimetre
Product weight	7.1 kilogram
Certifications	UL/CSA CE marking CSA Class No.: 3211-04 UL 60947-4-1 UL File No.: E29096 IEC 61373: Vibration and shock, tested for category 1 class B UL Category Control No.: NLDX IEC/EN 60947-4-1 VDE 0660 CSA File No. 1017510 North America (UL listed, CSA certified) EN 45545: Fire protection on railway vehicles
Product Tradename	DILM
Product Type	Contactor
Product Sub Type	None
Catalog Notes	Conventional thermal current Ith of main contacts (1-pole, open) at 60° EN 45545 - Fire protection on railway vehicles: Fire protection class of all plastics according to UL94: V-0 / plastic weight in total: 1.872 kg Contacts according to EN 50012

General information

Accessories	Fitting options auxiliary contacts: on the side: 2 x DILM820-XHI11(V)-SI; 2 x DILM820-XHI11-SA
Application	Contactors for Motors
Connection	Screw terminals
Degree of protection	IP00
Electromagnetic compatibility	Designed for operation in industrial environments. Its use in residential environments may cause radio-frequency interference, requiring additional noise suppression.
Fitted with:	Suppressor circuit in actuating electronics
Lifespan, electrical	100,000 Operations (at Condensor operation)
Lifespan, mechanical	10,000,000 Operations (AC operated) 10,000,000 Operations (DC operated)
Operating frequency	3000 mechanical Operations/h (AC operated) 200 Operations/h 3000 mechanical Operations/h (DC operated)
Overvoltage category	III
Pollution degree	3
Product category	Contactors
Protection	Finger and back-of-hand proof with terminal shroud or terminal block, Protection against direct contact when actuated from front (EN 50274)
Rated impulse withstand voltage (Uimp)	8000 V AC
Resistance	500 mΩ (Admissible transitional contact resistance - of the external control circuit device when actuating A11)
Shock resistance	8 g, N/C auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms 10 g, N/O auxiliary contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms 10 g, N/O main contact, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms
Signal level	5 V - 15 V, PLC signal level (A3 - A4) to IEC/EN 61131-2 (type 2), Magnet systems

Utilization category	AC-4: Normal AC induction motors: starting, plugging, reversing, inching AC-3: Normal AC induction motors: starting, switch off during running AC-1: Non-inductive or slightly inductive loads, resistance furnaces
Voltage type	AC/DC

Climatic environmental conditions

Altitude	Max. 2000 m
Ambient operating temperature - min	-40 °C
Ambient operating temperature - max	60 °C
Ambient operating temperature (enclosed) - min	-40 °C
Ambient operating temperature (enclosed) - max	40 °C
Ambient storage temperature - min	-40 °C
Ambient storage temperature - max	80 °C
Climatic proofing	Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30

Terminal capacities

Terminal capacity (busbar)	25 mm width, Main connection
Terminal capacity (copper band)	Fixing with flat cable terminal or cable terminal blocks; See terminal capacity for cable terminal blocks
Terminal capacity (flexible with cable lug)	50 - 240 mm^2
Terminal capacity (flexible with ferrule)	1 x (0.75 - 2.5) mm^2, Control circuit cables 2 x (0.75 - 2.5) mm^2, Control circuit cables
Terminal capacity (solid)	1 x (0.75 - 2.5) mm^2, Control circuit cables 2 x (0.75 - 2.5) mm^2, Control circuit cables
Terminal capacity (solid/stranded AWG)	18 - 14, Control circuit cables 2/0 - 500 MCM, Main cables
Terminal capacity (stranded with cable lug)	70 - 240 mm^2
Width across flats	16 mm
Screw size	M10, Terminal screw, Main connections M3.5, Terminal screw, Control circuit cables
Screwdriver size	2, Terminal screw, Control circuit cables, Pozidriv screwdriver
Tightening torque	1.2 Nm, Screw terminals, Control circuit cables 24 Nm, Main cable connection screw/bolt

Electrical rating

Inrush current	Max. 30 x Ie (peak)
Rated breaking capacity at 220/230 V	3000 A
Rated breaking capacity at 380/400 V	3000 A
Rated breaking capacity at 500 V	3000 A
Rated breaking capacity at 660/690 V	3000 A
Rated breaking capacity at 1000 V	950 A
Rated insulation voltage (Ui)	1000 V
Rated making capacity (cos phi to IEC/EN 60947)	3000 A
Rated operational current (Ie)	307 A at up to 525 V (Individual compensation, three-phase capacitors, open) 177 A at 690 V (Individual compensation, three-phase capacitors, open)
Rated operational current (Ie) at AC-3, 220 V, 230 V, 240 V	300 A
Rated operational current (Ie) at AC-3, 380 V, 400 V, 415 V	300 A
Rated operational current (Ie) at AC-3, 440 V	300 A
Rated operational current (Ie) at AC-3, 500 V	300 A
Rated operational current (Ie) at AC-3, 660 V, 690 V	185 A
Rated operational current (Ie) at AC-3, 1000 V	95 A
Rated operational current (Ie) at AC-4, 220 V, 230 V, 240 V	240 A
Rated operational current (Ie) at AC-4, 440 V	240 A
Rated operational current (Ie) at AC-4, 500 V	240 A
Rated operational current (Ie) at AC-4, 660 V, 690 V	150 A
Rated operational current (Ie) at AC-4, 1000 V	76 A
Rated operational power at AC-3, 240 V, 50 Hz	100 kW
Rated operational power at AC-3, 380/400 V, 50 Hz	160 kW
Rated operational power at AC-3, 415 V, 50 Hz	175 kW
Rated operational power at AC-3, 440 V, 50 Hz	185 kW
Rated operational power at AC-3, 500 V, 50 Hz	210 kW

Rated operational power at AC-3, 690 V, 50 Hz	170 kW
Rated operational power at AC-3, 1000 V, 50 Hz	132 kW
Rated operational power at AC-4, 220/230 V, 50 Hz	75 kW
Rated operational power at AC-4, 240 V, 50 Hz	82 kW
Rated operational power at AC-4, 415 V, 50 Hz	142 kW
Rated operational power at AC-4, 440 V, 50 Hz	150 kW
Rated operational power at AC-4, 500 V, 50 Hz	170 kW
Rated operational power at AC-4, 660/690 V, 50 Hz	137 kW
Rated operational voltage (Ue) at AC - max	1000 V
Rated operational power at AC-4, 1000 V, 50 Hz	108 kW
Safe isolation	1000 V AC, Between coil and contacts, According to EN 61140
Special purpose rating of definite purpose rating	360 A, FLA 480 V 60 Hz 3-ph, 100,000 cycles acc. to UL 1995, (UL/CSA) 300 A, FLA 600 V 60 Hz 3-ph, 100,000 cycles acc. to UL 1995, (UL/CSA) 1800 A, LRA 600 V 60 Hz 3-ph, 100,000 cycles acc. to UL 1995, (UL/CSA) 2160 A, LRA 480 V 60 Hz 3-ph, 100,000 cycles acc. to UL 1995, (UL/CSA)

Short-circuit rating

Short-circuit current rating (basic rating)	18 kA, SCCR (UL/CSA) 600 A, max. CB, SCCR (UL/CSA) 700 A, max. Fuse, SCCR (UL/CSA)
Short-circuit current rating (high fault at 480 V)	18/100 kA, Fuse, SCCR (UL/CSA) 700 A, Class L/450 A, Class J, max. Fuse, SCCR (UL/CSA) 65 kA, CB, SCCR (UL/CSA) 700 A, Class L, max. Fuse, SCCR (UL/CSA) 18 kA, Fuse, SCCR (UL/CSA) 250 A, max. CB, SCCR (UL/CSA)
Short-circuit current rating (high fault at 600 V)	18/100 kA, Fuse, SCCR (UL/CSA) 700 A, Class L/450 A, Class J, max. Fuse, SCCR (UL/CSA) 600 A, max. CB, SCCR (UL/CSA) 18 kA, Fuse, SCCR (UL/CSA) 18 kA, CB, SCCR (UL/CSA) 700 A, Class J, max. Fuse, SCCR (UL/CSA)
Short-circuit protection rating (type 1 coordination) at 1000 V	200 A gG/gL
Short-circuit protection rating (type 1 coordination) at 400 V	500 A gG/gL
Short-circuit protection rating (type 1 coordination) at 690 V	400 A gG/gL
Short-circuit protection rating (type 2 coordination) at 1000 V	160 A gG/gL
Short-circuit protection rating (type 2 coordination) at 400 V	400 A gG/gL
Short-circuit protection rating (type 2 coordination) at 690 V	315 A gG/gL

AC-1/Conventional thermal current Ith

Conventional thermal current ith at 40°C (3-pole, open)	490 A
Conventional thermal current ith at 50°C (3-pole, open)	438 A
Conventional thermal current ith at 55°C (3-pole, open)	418 A
Conventional thermal current ith at 60°C (3-pole, open)	400 A
Conventional thermal current ith (3-pole, enclosed)	315 A
Conventional thermal current ith of main contacts (1-pole, open)	1000 A
Conventional thermal current ith (1-pole, enclosed)	788 A

Switching capacity

Switching capacity (main contacts, general use)	350 A, Maximum motor rating (UL/CSA)
Switching capacity (auxiliary contacts, general use)	1 A, 250 V DC, (UL/CSA) 15 A, 600 V AC, (UL/CSA)
Switching capacity (auxiliary contacts, pilot duty)	P300, DC operated (UL/CSA) A600, AC operated (UL/CSA)

Magnet system

Behavior in marginal and transitional conditions	Sealing - Voltage interruptions (0 - 0.2 x Uc min ≤ 10 ms: Time is bridged successfully Sealing - Voltage drops (0.2 - 0.6 x Uc min ≤12 ms: Time is bridged successfully Sealing - Pick-up phase (0 - 0.7 x Uc min: Contactor does not switch on Sealing - Excess voltage (1.15 - 1.3 x Uc max): Contactor remains switched on Sealing - Voltage interruptions 0 - 0.2 x Uc min) > 10 ms: Drop-out of the contactor Sealing - Voltage drops (0.6 - 0.7 x Uc min: Contactor remains switched on Sealing - Voltage drops (0.2 - 0.6 x Uc min) > 12 ms: Drop-out of the contactor Sealing - Pick-up phase (0.7 x Uc min - 1.15 x Uc max): Contactor switches on with certainty
Drop-out voltage	0.2 x US max - 0.6 x US min, DC operated AC operated: 0.2 x US max - 0.6 x US min, AC operated
Duty factor	100 %
Pick-up voltage	0.7 - 1.15 V DC x Us

	0.7 - 1.15 V AC x Us
Power consumption	Control transformer with uk ≤ 6% 110 kW
Power consumption, pick-up, 50 Hz	380 VA, Pull-in power, Coil in a cold state and 1.0 x Us 250 W, Pull-in power, Coil in a cold state and 1.0 x Us
Power consumption, pick-up, 60 Hz	380 VA, Pull-in power, Coil in a cold state and 1.0 x Us 250 W, Pull-in power, Coil in a cold state and 1.0 x Us
Power consumption, sealing, 50 Hz	10.5 VA, Coil in a cold state and 1.0 x Us 5.5 W, Coil in a cold state and 1.0 x Us
Power consumption, sealing, 60 Hz	5.5 W, Coil in a cold state and 1.0 x Us 10.5 VA, Coil in a cold state and 1.0 x Us
Rated control supply voltage (Us) at AC, 50 Hz - min	110 V
Rated control supply voltage (Us) at AC, 50 Hz - max	250 V
Rated control supply voltage (Us) at AC, 60 Hz - min	110 V
Rated control supply voltage (Us) at AC, 60 Hz - max	250 V
Rated control supply voltage (Us) at DC - min	110 V
Rated control supply voltage (Us) at DC - max	250 V
Switching time (AC operated, make contacts, closing delay) - max	100 ms
Switching time (AC operated, make contacts, opening delay) - max	110 ms
Motor rating	
Assigned motor power at 200/208 V, 60 Hz, 3-phase	100 HP
Assigned motor power at 230/240 V, 60 Hz, 3-phase	125 HP
Assigned motor power at 460/480 V, 60 Hz, 3-phase	250 HP
Assigned motor power at 575/600 V, 60 Hz, 3-phase	300 HP
Contacts	
Number of auxiliary contacts (normally closed contacts)	2
Number of auxiliary contacts (normally open contacts)	2
Number of contacts (normally closed contacts)	2
Number of contacts (normally open contacts)	2
Design verification	
Equipment heat dissipation, current-dependent Pvid	21 W
Heat dissipation capacity Pdiss	0 W
Heat dissipation per pole, current-dependent Pvid	7 W
Rated operational current for specified heat dissipation (In)	300 A
Static heat dissipation, non-current-dependent Pvs	5.5 W
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Meets the product standard's requirements.
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of assemblies	Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances	Meets the product standard's requirements.
10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
10.8 Connections for external conductors	Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength	Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage	Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material	Is the panel builder's responsibility.
10.10 Temperature rise	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility	Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Power contactor, AC switching (EC000066)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Contactor (LV) / Power contactor, AC switching (ecl@ss13-27-37-10-03 [AAB718020])		
Rated control supply voltage AC 50 Hz	V	110 - 250
Rated control supply voltage AC 60 Hz	V	110 - 250
Rated control supply voltage DC	V	110 - 250
Voltage type for actuating		AC/DC
Number of normally closed contacts as main contact		0
Number of normally open contacts as main contact		3
Type of electrical connection of main circuit		Rail connection
Operating voltage AC 50 Hz	V	110 - 250
Operating voltage AC 60 Hz	V	110 - 250
Rated operation current Ie at AC-1, 400 V	A	
Rated operation current Ie at AC-3, 400 V	A	300
Rated operation power at AC-3, 400 V	kW	160
Rated operation current Ie at AC-4, 400 V	A	240
Rated operation power at AC-4, 400 V	kW	132
Rated operation power NEMA	kW	186
Number of auxiliary contacts as normally open contact		2
Number of auxiliary contacts as normally closed contact		2
Modular version		No
Width	mm	140
Height	mm	189
Depth	mm	208

© 04/2023 by Eaton Industries GmbH