DATASHEET - NHI-E-11-PKZ0



Standard auxiliary contact, NHI-E, 1 N/O, 1 NC, Can be fitted to the front, Screw terminals

Part no.	**NHI-E-11-PKZ0**
	082882
EL Number (Norway)	**4355153**

General specifications

Product name	Eaton Moeller® series NHI Accessory Standard auxiliary contact
Part no.	NHI-E-11-PKZ0
EAN	4015080828822
Product Length/Depth	12 millimetre
Product height	35 millimetre
Product width	45 millimetre
Product weight	0.016 kilogram
Certifications	UL File No.: E36332 CSA File No.: 165628 UL CSA UL Category Control No.: NLRV CE UL 508 CSA-C22.2 No. 14 CSA Class No.: 3211-05 IEC/EN 60947-4-1
Product Tradename	NHI
Product Type	Accessory
Product Sub Type	Standard auxiliary contact
Catalog Notes	Can be fitted to the front. Terminal designation differs to that of an auxiliary contact that can be fitted to the side

General information

Electric connection type	Screw connection
Lifespan, electrical	100,000 Operations
Lifespan, mechanical	100,000 Operations
Model	Top mounting
Mounting method	Front fastening
Overvoltage category	III
Pollution degree	3
Product category	Accessories
Rated impulse withstand voltage (Uimp)	4000 V AC
Used with	Motor protective circuit-breaker

Climatic environmental conditions

Ambient operating temperature - min	-25 °C
Ambient operating temperature - max	55 °C

Terminal capacities

Terminal capacity (solid/flexible with ferrule)	0.75 - 1.5 mm^2
Terminal capacity (solid/stranded AWG)	18 - 16, Screw terminals

Electrical rating

Rated operational current (Ie) at AC-15, 220 V, 230 V, 240 V	1 A
Rated operational current (Ie) at DC-13, 24 V	2 A
Rated operational voltage (Ue) at AC - max	440 V
Rated operational voltage (Ue) at DC - max	250 V
Safe isolation	440 V, Between auxiliary contacts and main contacts, According to EN 61140
Short-circuit protection rating without welding	10 A gG/gL, Fuse, Auxiliary contacts

Switching capacity

Switching capacity (auxiliary contacts, general use)	0.5 A, 250 V DC, (UL/CSA)
Switching capacity (auxiliary contacts, pilot duty)	E150, AC operated (UL/CSA)

Contacts			
Number of contacts (change-over contacts)			0
Number of contacts (normally closed contacts)			1
Number of contacts (normally open contacts)			1
Design verification			
Equipment heat dissipation, current-dependent Pvid			0 W
Heat dissipation capacity Pdiss			0 W
Heat dissipation per pole, current-dependent Pvid			0.01 W
Rated operational current for specified heat dissipation (In)			1 A
Static heat dissipation, non-current-dependent Pvs			0 W
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			Meets the product standard's requirements.
10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of assemblies			Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Auxiliary contact block (EC000041)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Auxiliary switch block (ecl@ss13-27-37-13-02 [AKN342018])

Number of contacts as change-over contact			0
Number of contacts as normally open contact			1
Number of contacts as normally closed contact			1
Number of fault-signal switches			0
Rated operation current Ie at AC-15, 230 V		A	1
Type of electric connection			Screw connection
Model			Clip-on
Mounting method			Front fastening
Lamp holder			None

© 04/2023 by Eaton Industries GmbH